



NBUS

MOVING NELSON FORWARD

BIKES ON BUSES

LOADING YOUR BIKE

Remove any loose items from bike that could fall off while bus is moving. Let driver know you're going to load your bike.

STEP 1 >

Squeeze bike rack handle up to release. Lower rack.



STEP 2 >

Lift bike onto rack with front wheel facing toward yellow support arm and fit wheels into clearly labelled slots.



STEP 3 >

Raise support arm over front tyre so the hook rests on the top of the front wheel.



Please remember loading and unloading your bike is up to you. Always load or unload your bike from the front of the bike rack.



NBUS

MOVING NELSON FORWARD

BIKES ON BUSES

UNLOADING YOUR BIKE

Let the driver know you will be unloading your bike and exit via front doors.

STEP 1 >

Unhook and lower support arm from front tyre and lift your bike from the rack.



STEP 2 >

If no-one else is using the rack, squeeze handle and fold bike rack back up.



BIKE RACK RULES

- If you're taking the bus, it's free to use the bike rack
- Cyclists are responsible for loading and unloading their bike
- The bike rack takes two bikes at a time. If it's full, wait for the next bus
- Racks are designed to carry bikes with wheels larger than 16" diameter
- The maximum insured value of any bike on the rack is \$1500.